



# SPRINGFIELD ARMORY®

# SAINT™

## 5.56

## SPECIFICATIONS

<b>WEIGHT:</b>	6lbs 11oz	<b>TRIGGER GUARD:</b>	BRAVO COMPANY TRIGGER GUARD
<b>LENGTH:</b>	35.5" FULLY EXTENDED / 32.25" COLLAPSED	<b>PISTOL GRIP:</b>	BRAVO COMPANY MOD 3
<b>UPPER RECEIVER:</b>	TYPE III HARD COAT ANODIZED AIRCRAFT GRADE 7075 T6 ALUMINUM FLAT TOP UPPER RECEIVER WITH FORWARD ASSIST AND M4 FEED RAMPS	<b>HANDGUARD:</b>	NEW, EXCLUSIVE BRAVO COMPANY, KEYMOD, PKMR
<b>LOWER RECEIVER:</b>	TYPE III HARD COAT ANODIZED AIRCRAFT GRADE 7075 T6 ALUMINUM LOWER RECEIVER WITH ACCU-TITE™ TENSION SYSTEM	<b>BUTT STOCK:</b>	BRAVO COMPANY 6 POSITION
<b>BARREL:</b>	16" HIGH QUALITY CHROME MOLY VANADIUM BARREL CHAMBERED IN 5.56 NATO WITH A 1:8 RH TWIST, MELONITE® TREATMENT APPLIED TO CHAMBER, BORE AND EXTERNAL SURFACES	<b>BUFFER ASSEMBLY:</b>	CARBINE "H" HEAVY TUNGSTEN BUFFER
<b>GAS SYSTEM:</b>	DIRECT IMPINGEMENT MID-LENGTH GAS SYSTEM WITH A .750 DIAMETER GAS BLOCK / FRONT SIGHT BASE	<b>RECEIVER EXTENSION:</b>	MIL-SPEC CARBINE RECEIVER EXTENSION MANUFACTURED FROM 7075 T6 TYPE III HARD ANODIZED ALUMINUM
<b>TRIGGER:</b>	SPRINGFIELD ARMORY® PROPRIETARY, ENHANCED NICKEL BORON COATED GI SINGLE STAGE TRIGGER	<b>CHARGING HANDLE:</b>	GI STYLE
<b>SIGHTS:</b>	SPRINGFIELD ARMORY® LOW PROFILE FLIP-UP, DUAL APERTURE REAR SIGHT, 1/2 MOA WINDAGE ADJUSTMENT	<b>BOLT CARRIER GROUP:</b>	M16 BCG W/ CARPENTER 158 STEEL BOLT, SHOT PEENED AND MAGNETIC PARTICLE INSPECTED TO ENSURE IT MEETS MIL-SPEC DURABILITY REQUIREMENTS
		<b>MAGAZINE:</b>	1 - 30 ROUND MAGPUL PMAG GEN M3