



SAINT
5.56

CALIFORNIA MODEL

SPECIFICATIONS (ST916556BCA)

WEIGHT: 6lbs 13oz

LENGTH: 35.75"

UPPER RECEIVER: FORGED TYPE III HARD COAT ANODIZED AIRCRAFT GRADE 7075 T6 ALUMINUM FLAT TOP UPPER RECEIVER WITH FORWARD ASSIST AND M4 FEED RAMPS

LOWER RECEIVER: FORGED TYPE III HARD COAT ANODIZED AIRCRAFT GRADE 7075 T6 ALUMINUM LOWER RECEIVER WITH ACCU-TITE™ TENSION SYSTEM

BARREL: 16" HIGH QUALITY CHROME MOLY VANADIUM BARREL CHAMBERED IN 5.56 NATO WITH A 1:8 RH TWIST, MELONITE® TREATMENT APPLIED TO CHAMBER, BORE AND EXTERNAL SURFACES, SA MUZZLE BREAK

GAS SYSTEM: DIRECT IMPINGEMENT MID-LENGTH GAS SYSTEM WITH A .750 DIAMETER GAS BLOCK / FRONT SIGHT BASE

TRIGGER: SPRINGFIELD ARMORY® PROPRIETARY, ENHANCED NICKEL BORON COATED GI SINGLE STAGE TRIGGER

MSRP: \$998

SIGHTS: SPRINGFIELD ARMORY® LOW PROFILE FLIP-UP, DUAL APERTURE REAR SIGHT, 1/2 MOA WINDAGE ADJUSTMENT

TRIGGER GUARD: BRAVO COMPANY TRIGGER GUARD

HANDGUARD: NEW, EXCLUSIVE BRAVO COMPANY, KEYMOD, PKMR

STOCK: SURVIVOR SYSTEM STOCK

BUFFER ASSEMBLY: CARBINE "H" HEAVY TUNGSTEN BUFFER

RECEIVER EXTENSION: MIL-SPEC DIMENSION CARBINE RECEIVER EXTENSION MANUFACTURED FROM 7075 T6 TYPE III HARD ANODIZED ALUMINUM

CHARGING HANDLE: GI STYLE

BOLT CARRIER GROUP: M16 BCG W/ CARPENTER 158 STEEL BOLT, SHOT PEENED AND MAGNETIC PARTICLE INSPECTED TO ENSURE IT MEETS THE MOST DEMANDING DURABILITY REQUIREMENTS

MAGAZINE: 1 - 10 ROUND MAGPUL PMAG