



SAINT

5.56

FREE FLOAT HANDGUARD
CALIFORNIA MODEL

SPECIFICATIONS (ST916556BFFHCA)

WEIGHT: 7 LBS 3 OZ

LENGTH: 35.5"

UPPER RECEIVER: FORGED TYPE III HARD COAT ANODIZED AIRCRAFT GRADE 7075 T6 ALUMINUM FLAT TOP UPPER RECEIVER WITH FORWARD ASSIST AND M4 FEED RAMPS

LOWER RECEIVER: FORGED TYPE III HARD COAT ANODIZED AIRCRAFT GRADE 7075 T6 ALUMINUM LOWER RECEIVER WITH ACCU-TITE™ TENSION SYSTEM

BARREL: 16" HIGH QUALITY CHROME MOLY VANADIUM BARREL CHAMBERED IN 5.56 NATO WITH A 1:8 RH TWIST, MELONITE® TREATMENT APPLIED TO CHAMBER, BORE AND EXTERNAL SURFACES

GAS SYSTEM: DIRECT IMPINGEMENT MID-LENGTH GAS SYSTEM WITH A LOW PROFILE GAS BLOCK

TRIGGER: SPRINGFIELD ARMORY® PROPRIETARY, ENHANCED NICKEL BORON COATED GI SINGLE STAGE TRIGGER

SIGHTS: SPRINGFIELD ARMORY® LOW PROFILE FLIP-UP, DUAL APERTURE SIGHTS, 1/2 MOA WINDAGE ADJ & FLIP-UP FRONT, 1/2 MOA ELEVATION ADJ.

TRIGGER GUARD: BRAVO COMPANY TRIGGER GUARD

HANDGUARD: M-LOK ALUMINUM SA PROPRIETARY FREE FLOAT WITH SA LOCKING TABS

BUTT STOCK: SURVIVOR SYSTEM STOCK

BUFFER ASSEMBLY: CARBINE "H" HEAVY TUNGSTEN BUFFER

RECEIVER EXTENSION: MIL-SPEC DIMENSION CARBINE RECEIVER EXTENSION MANUFACTURED FROM 7075 T6 TYPE III HARD ANODIZED ALUMINUM

CHARGING HANDLE: GI STYLE

BOLT CARRIER GROUP: M16 BCG W/ CARPENTER 158 STEEL BOLT, SHOT PEENED AND MAGNETIC PARTICLE INSPECTED TO ENSURE IT MEETS THE MOST DEMANDING DURABILITY REQUIREMENTS

MAGAZINE: 1 - 10 ROUND MAGPUL PMAG

MUZZLE BREAK: SA CALIFORNIA LEGAL

MSRP: \$1,135